

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in this application.

1. (Currently Amended) A roller device for a movable point of frog, ~~including~~
comprising
a sliding strip, ~~and~~
at least one roller (11), and
at least one roller bearing fixed to a stationary part of ~~the~~ a switch, ~~characterized in that~~
wherein
~~the roller(s) said at least one roller (11) is/are~~ is mounted on ~~an~~ a first arm (9) of a
double-armed lever (10),
~~that the~~ a pivot bearing (12) of the lever (10) is arranged in a support (13) connected with
a stationary part of the switch, and
~~that the~~ a second arm (18) of the double-armed lever (10) facing away from the ~~roller(s)~~
at least one roller (11) ~~, of the double-armed lever (10)~~ is pivotable against a spring (19) with
adjustable spring power.
2. (Currently Amended) A roller device according to claim 1, ~~characterized in that~~
wherein the lever arm ratio ratios of the double-armed levers (10) of a switch is are each selected
to be identical, and the ~~respectively shorter~~ first lever arm (9) is respectively shorter than the
second lever arm (18), and carries the ~~roller(s)~~ at least one roller (11).

3. (Currently Amended) A roller device according to claim 1 ~~or 2, characterized in that~~ wherein the pivot bearing (12) of the lever (10) is ~~provided~~ arranged in a substantially U-shaped support (13) ~~and, in particular, in or on the side cheeks of said support (13).~~

4. (Currently Amended) A roller device according to claim 1, ~~2 or 3, characterized in that the~~ wherein a lever arm ratio of the double-armed lever (10) is 2:3 to 1:3, preferably 1:2.

5. (Currently Amended) A roller device according to ~~any one of claims 1 to 4, characterized in that~~ claim 1, wherein the second lever arm (18) is designed to be cranked.

6. (Currently Amended) A roller device according to ~~any one of claims 1 to 5, characterized in that~~ claim 1, wherein the support (13) is fixed to ~~the~~ wing rails (2, 3) or to the supporting structure (4, 5) of the switch, and ~~that the~~ an adjustment device (20) for the spring (19) in top view is arranged outside the wing rails (2, 3) or the supporting structure (4, 5), respectively.

7. (New) A roller device according to claim 1, wherein the pivot bearing (12) of the lever (10) is arranged in or on side cheeks of said support (13).

8. (New) A roller device according to claim 1, wherein a lever arm ratio of the double-armed lever (10) is 1:2.

9. (New) A roller device according to claim 2, wherein the pivot bearing (12) of the lever (10) is arranged in a substantially U-shaped support (13).

10. (New) A roller device according to claim 2, wherein a lever arm ratio of the double-armed lever (10) is 2:3 to 1:3.

11. (New) A roller device according to claim 3, wherein a lever arm ratio of the double-armed lever (10) is 2:3 to 1:3.

12. (New) A roller device according to claim 7, wherein a lever arm ratio of the double-armed lever (10) is 2:3 to 1:3.

13. (New) A roller device according to claim 2, wherein the second lever arm (18) is designed to be cranked.

14. (New) A roller device according to claim 3, wherein the second lever arm (18) is designed to be cranked.

15. (New) A roller device according to claim 4, wherein the second lever arm (18) is designed to be cranked.

16. (New) A roller device according to claim 7, wherein the second lever arm (18) is designed to be cranked.

17. (New) A roller device according to claim 8, wherein the second lever arm (18) is designed to be cranked.

18. (New) A roller device according to claim 2, wherein the support (13) is fixed to wing rails (2, 3) or to supporting structure (4, 5) of the switch, and an adjustment device (20) for the spring (19) in top view is arranged outside the wing rails (2, 3) or the supporting structure (4, 5), respectively.

19. (New) A roller device according to claim 3, wherein the support (13) is fixed to wing rails (2, 3) or to supporting structure (4, 5) of the switch, and an adjustment device (20) for the spring (19) in top view is arranged outside the wing rails (2, 3) or the supporting structure (4, 5), respectively.

20. (New) A roller device according to claim 4, wherein the support (13) is fixed to wing rails (2, 3) or to supporting structure (4, 5) of the switch, and an adjustment device (20) for the spring (19) in top view is arranged outside the wing rails (2, 3) or the supporting structure (4, 5), respectively.

21. (New) A roller device according to claim 5, wherein the support (13) is fixed to wing rails (2, 3) or to supporting structure (4, 5) of the switch, and an adjustment device (20) for the spring (19) in top view is arranged outside the wing rails (2, 3) or the supporting structure (4, 5), respectively.

22. (New) A roller device according to claim 7, wherein the support (13) is fixed to wing rails (2, 3) or to supporting structure (4, 5) of the switch, and an adjustment device (20) for the spring (19) in top view is arranged outside the wing rails (2, 3) or the supporting structure (4, 5), respectively.

23. (New) A roller device according to claim 8, wherein the support (13) is fixed to wing rails (2, 3) or to supporting structure (4, 5) of the switch, and an adjustment device (20) for the spring (19) in top view is arranged outside the wing rails (2, 3) or the supporting structure (4, 5), respectively.